

Application Serial No. 10/823,105
Reply to office action of July 16, 2007

PATENT
Docket: CU-3682

RECEIVED
CENTRAL FAX CENTER

DEC 03 2007

Amendments To The Claims

The listing of claims presented below will replace all prior versions, and listings, of claims in the application.

Listing of claims:

1-7. (cancelled)

8. (currently amended) A ~~[[The]]~~ liquid crystal device element ~~according to claim 7 comprising:~~

a pair of parallel substrates;

conductive layers provided respectively on facing inner surfaces of these substrates;

liquid crystal alignment layers provided respectively with pre-tilt angle on facing inner surfaces of these conductive layers, and

a liquid crystal layer formed in between these pair of liquid crystal alignment layers,

wherein liquid crystal-soluble particles are dissolved or dispersed in the liquid crystal layer,

wherein each of the liquid crystal-soluble particles comprises a core having a diameter smaller than 100 nm and comprising one or a plurality of nanoparticles, and a protective layer comprising liquid crystal molecules or liquid crystal-like molecules provided on a periphery of the core,

wherein a control circuit of applying voltage, while modulating at least frequency

Application Serial No. 10/823,105
Reply to office action of July 16, 2007

PATENT
Docket: CU-3682

among frequency and voltage, is provided on the conductive layer for varying light transmittance of the liquid crystal layer, and

wherein under a constant applied voltage, an electro-optical response is turned on by switching the frequency of applied electric field from low frequency to high frequency, and the electro-optical response is turned off by switching the frequency from high frequency to low frequency.

9. (original) The liquid crystal device element according to claim 8, wherein a time constant of response concerning turning the electro-optical response on and off is in a range of 0.1 ms to 10 ms.

10. (original) The liquid crystal device element according to claim 8, wherein a frequency modulation range of the electro-optical response is in a range of 20 Hz to 100 kHz.

11. (original) The liquid crystal device element according to claim 8, wherein the nanoparticle constituting the liquid crystal-soluble particle is at least one kind of metal atom selected from Ag, Pd, Au, Pt, Rh, Ru, Cu, Fe, Co, Ni, Sn and Pb.

12. (original) A method for driving a liquid crystal device element, wherein the liquid crystal device element according to claim 8 is driven by using an active matrix mode.

13. (new) The liquid crystal device element according to claim 8, wherein the

Application Serial No. 10/823,105
Reply to office action of July 16, 2007

PATENT
Docket: CU-3682

short axis width of the liquid crystal molecule or liquid crystal-like molecule is
equal to or less than the diameter of the core.